

Product Category	Thicknees/Specification	Standard	Master
Creasing Rule (Steel)	Any Thickness in stock/Standard Shape	7 ~ 9 days	2 days (1.5days)
Creasing Rule (Iron)	Any Thickness in stock/Standard Shape		
Cutting Rules	0.7 ~ 1.4		
NCA (Center Bevel)	0.4 ~ 1.4		
NCC(Side Bevel)	0.45 ~ 3PT		
Creasing Rules(Steel)Dull Point 0.2~0.4		1 0 ~ 1 4 days	3 days
Form Rules			
Form Perforating Rules			
NCD (Double Long Bevel)	0.45 ~		
NCF(Side Double long Bevel)	0.45 ~		
NCC(Side Bevel)	1.2 ~		
NC Perforating Rules			
Perforating Rules	1.2 ~		
Creasing Rules(Steel)Dull Point 0.2~0.4	Special Shape		
Cut Crease Rules	0.7 ~ 1.4		
(NC) Label Rules			
M I R			
NCD-MIR (MIR Double long Bevel)			
Perforating Label Rules			
MIR Label Rules			
Creasing Rule (Iron)/Stripping steel Rule	3.0 Notched		
Creasing Rules	Notched		
(NC) Cut Crease Rules	0.7 ~ 1.4		
NC Edge Wave Rules			
Z-MIR (Long Bevel Both Bevels:Mirror Finish)			
NCD Edge Wave Rules			
NCA (Center Bevel)	Notched		